



Rack-Mount (1U) Headset Station with Strobe

Performance: The HS-2R/L is a combination of two well established products, the HS-1 headset station and the xenon (strobe) light elements from our Blazon series. Like all HS versions, the HS-2R/L provides the same facilities as our BP-1 portable headset stations (belt packs) but in this case, in a 1U rack mount cabinet.



Frequency response has been carefully shaped to optimize both intelligibility and long-term listening comfort. A mic limiter circuit reduces overload distortion. The high bridging impedance ensures that system and sidetone levels do not vary as other stations are switched in and out of the circuit.

The front panel contains controls for switching the microphone on and off, for controlling listening level, and for signaling. A recessed, screwdriver-adjust control is provided for varying the level of the user's voice to be heard in his own earphone (sidetone). The HS-2R/L has 3-pin XLR connectors on the rear panel for connection of the station and daisy chaining on to the next station in the circuit. The headset or handset connects to the station via a front-panel 4-pin XLR connector. The xenon lamp on the front panel lights whenever anyone on the same circuit presses their signal light button. A built-in timer keeps the signal light circuit activated for 4 seconds and the lamp has a 2Hz frequency, providing 7 to 8 flashes each time. The xenon may be switched off.

Durability: The HS2R/L is constructed to withstand the rugged use associated with touring.

Value: Simplicity of construction affords the use of high quality components while maintaining a favorable cost/benefit ratio.

Compatibility: The HS-2R/L is compatible with Clear-Com[®] and other lesser-known (unbalanced 200Ω) headset intercom systems.

Technical Specifications: (Subject to change without notice)

Power requirement: 24 ~ 30 VDC, 10mA quiescent, 40mA max.	Sidetone rejection: 50dB
(with signal lamp lit) 70mA with xenon charging	Audio bridging impedance: 200 Ω unbalanced
Headphone output: 8 ~ 4K Ω acceptable, 200 Ω ideal.	Size: 19 x 1.75 x 7.0 in.
Microphone input: 200 ~ 600 Ω dynamic or 1.8K electret	Weight: 8.5 oz. (2.41 Kg)

Production Intercom Inc.

P.O. Box 3247, Barrington, IL 60011-3247
Voice: (847) 381-5350 Fax: (847) 381-4360 Sales & Technical Assistance (US & Can): (800) 562-5872
e-mail: info@beltpack.com Web: beltpack.com